

## PRODUCT INFORMATION

- Luft type vent, mounted in the fireplace housing.
- Made of 1,5mm thick steel.
- Available in RAL colours, semi-gloss: black 9005, white 9016, creme 9001, graphite 7024 (powder painting).
- Supply function at assembly under the fireplace insert (ventilation openings are placed up).
- Exhaust function at assembly over the fireplace insert (ventilation openings are placed down).

## VENT SLIM 12

Product code	External dimensions					Mounting holes dimensions		Active area of grids	Product code	External dimensions					Mounting holes dimensions		Active area of grids
	A	B	C	D	E	A	D1			D2	E	A	B1	B2	C	D1	
SL-12x20-SI	120	200	134	175	95	153		153	SL-12x56x56	120	560	560	97	546	546	95	981
SL-12x40-SI	120	400	134	375	95	333		333	SL-12x60x40L L - in / R - out	120	600	400	97	586	386	95	873
SL-12x60-SI	120	600	134	575	95	513		513	SL-12x60x40R R - in / L - out	120	400	600	97	386	586	95	873
SL-12x80-SI	120	800	134	775	95	693		693	SL-12x80-45L L - in / R - out	120	800	450	97	786	436	95	1098
SL-12x100-SI	120	1000	134	975	95	873		873	SL-12x80x45R R - in / L - out	120	450	800	97	436	786	95	1098

